



Features and Benefits


- Manufactured from EPDM or silicone rubber, ROOFJACK is compounded for maximum resistance to ozone, UV light, & temperature extremes.
- Flexible aluminum base will allow the flashing to conform to any metal roof configuration. Pipe location can be centered in the flat of the panel or the rib. Urethane sealant & self-drilling screws complete the installation
- ROOFJACK are well marked so they can easily be cut with shears to fit exactly the pipe size used.
- ROOFJACK are available in Black or Gray EPDM as well as Red or Gray high temperature Silicone.

RoofjackRD™



High Temperature Silicone is Now Available in Gray

EASY INSTALLATION



1. Choose pipe opening and trim



2. Slide over pipe



3. Form to roof profile



4. Apply sealant



5. Fasten to complete

	PIPE SIZE	BASE DIAMETER	COLOR MATERIAL	CARTON QUANTITY	WEIGHT PER CARTON
#1	1/4" -2-1/2"	4.75" (120.7mm)	Black/Gray EPDM & Red/Gray Silicone	15	2.5
#2	1-3/4"-3"	6.21" (157.7mm)	Black/Gray EPDM & Red/Gray Silicone	15	4.5
#3	1/4"-5"	7.74" (196.6mm)	Black/Gray EPDM & Red/Gray Silicone	15	7.5
#4	3"-6-1/4"	9.26" (235.2mm)	Black/Gray EPDM & Red/Gray Silicone	10	8.0
#5	4-1/4"-7-3/4"	10.75" (273.0mm)	Black/Gray EPDM & Red/Gray Silicone	10	9.5
#6	5" - 9"	12.50" (317.5mm)	Black/Gray EPDM & Red/Gray Silicone	10	12.0
#7	6" - 11"	14.60" (370.8mm)	Black/Gray EPDM & Red/Gray Silicone	10	15.5
#8	7" - 13"	16.5" (419.1mm)	Black/Gray EPDM & Red/Gray Silicone	5	12.8
#9	9" - 19"	25.25" (641.1mm)	Black/Gray EPDM & Red/Gray Silicone	5	19.3

	EPDM 500	SILICONE
Advanced Ozone Resistance Tested to...	70 hr @500 pphm	70 hr @ 500 pphm
High Temperature Resistance Tested to Intermittent Continuous	+135°C (+275°F) +100°C (+212°F)	+260°C (+500°F) +225°C (+500°F)
Low Temperature Resistance tested to...	-55°C (-65°F)	-74°C (-100°F)
Tensile Set Maximum...	10MPa (1450psi)	5MPa (700psi)
Compression Set Maximum...	25%	50%